

Feeding

Schuitemaker

Schuitemaker

Master your Forage



Schuitemaker

Feed daily

reliably and with ease

As a livestock farmer, you want to be able to rely on the machines you use every day.

Schuitemaker feeding machines, known as Feedo and Amigo, have been a household name for more than 40 years. The machines are distinguished by simplicity and durability. Efficient feeding with low fuel consumption.

The quality and finish of the machines are among the absolute best in the market and they are purpose-built for livestock farmers who want to feed their livestock reliably and responsibly. Quality and fast feeding, **today and tomorrow.**



The easy Amigo with flexible loading system

Further developed with the changing ensilage process in mind. The ideal block and bale feeder because of its low operating and maintenance costs, compact construction and easy operation.

The Schuitemaker Amigo is available in different versions to suit the type of stall, silage and work. The unique patented rake (20S) or double beater (30W/ 40S) combination ensures a constant feed flow on the cross-conveyor. For even better cutting action, the beater of the Amigo can optionally be equipped with knives.

The wear-resistant tailgate can be used to load both round and square bales, as well as pre-cut silage blocks. So, depending on the ration, there is no need to use a second tractor or shovel. Thus, the Amigo helps save on operating costs.



The multi-purpose Feedo

optimum mixing and
feeding results

For years, the Schuitemaker Feedo has been a leading forage feeder wagon used to mix and dose different types of feed.

The feed is distributed evenly and with retention of structure thanks to the special Feedo distribution beaters. Good feed quality thanks to dosing, with minimum fuel consumption and no waiting time.

The machine can unload either on the left or right side, and the cross discharge conveyor can be supplied in a front or rear unloading version.

Because the Feedo is available in different sizes and can be equipped with a wide variety of options, it is suitable for feeding in any barn.



Optimal feed composition

tailored to the cow's needs

Because the Feedo offers the possibility of loading the different products in layers, this machine is ideally suited to optimising ration composition.

All Schuitemaker Feedos and the Amigo 30/40 can optionally be equipped with a weighing system. This allows the feed composition to be tailored exactly to the cow's needs. This leads to high milk production, healthy cows and cost savings through efficient use of by-products.



Technical specifications

TYPE:		AMIGO			FEEDO												
		20S	30W	40S	Feedo 50-8	Feedo 50-11	Feedo 60-10	Feedo 60-13	Feedo 60L-9	Feedo 60L-13	Feedo 80-13	Feedo 80-18	Feedo 100-15	Feedo 100-20	Feedo 170-23	Feedo 170-30	Feedo 170-32
Volume DIN, standard	m ³	3,5	5	7	8	11	10	13	9	13	13	18	15	20	23	30	32
Load capacity	kg	2.000	3.000	4.000	4.800	6.350	5.700	7.650	5.700	7.650	8.000	10.000	9.000	10.000	13.000	14.000	14.000
Box dimensions	cm	194x190 x90	274x200 x90	345x200 x120	400x160 x120	400x160 x170	400x190 x120	400x190 x170	440x160 x120	440x160 x170	520x190 x125	520x190 x175	520x220 x125	520x220 x175	640x220 x165	820x220 x165	690x220 x215
Total dimensions	cm	377x230 x190	503x230 x223	566x230 x223	614x190 x236	614x190 x286	614x220 x239	614x220 x289	654x190 x239	654x190 x289	734x220 x240	734x220 x290	734x250 x238	734x250 x288	844x250 x282	844x250 x322	883x250 x353
Tires		6x9-10pr	10X15-14pr	10X15-14pr	13x16-10pr	13x16-10pr	12,5x18- 12pr	12,5x18- 12pr	12,5x18- 12pr	12,5x18- 12pr	15x18-16pr	15x18-16pr	500/50-17	500/50-17	Dunlop 435-50- 19,5	Dunlop 435-50- 19,5	560/45 R22,5
Discharge height	cm	47	70	70	94	94	97	97	97	97	94	94	91	91	93	93	110
Width of cross-conveyor	l/min	-	-	-	146	146	149	149	149	149	146	146	143	143	145	145	-

Options	AMIGO			FEEDO													
	20S	30W	40S	Feedo 50-8	Feedo 50-11	Feedo 60-10	Feedo 60-13	Feedo 60L-9	Feedo 60L-13	Feedo 80-13	Feedo 80-18	Feedo 100-15	Feedo 100-20	Feedo 170-23	Feedo 170-30	Feedo 170-32	
Speed control for cross-conveyor	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	●
Bowden cable control	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	-
Electric control	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	●
Weighing system	-	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	●
Hydraulic folding cross-conveyor	-	-	-	○	○	○	○	○	○	○	○	○	○	○	○	○	-
Split cross-conveyor	-	-	-	○	○	○	○	○	○	○	○	○	○	○	○	○	-
Protective edge on side walls	-	-	-	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Knives for Amigo	○	○	○	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Closed beater Feedo with knives	-	-	-	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Lighting	-	-	-	○	○	○	○	○	○	○	○	○	○	○	○	○	○
UK Feedo-package, parking skid instead of hydr. jack, braked axle *)	-	-	-	○	○	○	○	○	○	○	○	○	○	○	○	○	○

*) For the UK-market to choose the UK-Feedo-package For Feedo 50 - 80 is necessary. Feedo's 100-170 do have standard hydr braked axles.

Explanation of symbols: ● = Standard ○ = Optional - = Not available

All data has been compiled with the greatest possible care but are non-binding. Changes in construction/design are always possible.

Schuitemaker

Master your Forage



Morsweg 18 T +31 (0) 548 - 51 4125
7461 AG Rijssen E info@svgroun.nl

sr-schuitemaker.nl • svgroun.nl

